

ENERPAC 700 BAR HYDRAULIC-SETS

**GENERAL PURPOSE CYLINDER & HAND PUMP SETS**

FREE G2535L GAUGE AND GA-3 ADAPTOR
WITH ANY SET PURCHASED FOR SAFE OPERATIONS

- For maximum versatility
- Single-acting, spring return cylinder
- 25-50 ton capacity, 26-362 mm stroke
- With two speed lightweight or steel hand pump and 1,8 metres safety hose

SET PRICE STARTS AT :

\$860,-

**LOW HEIGHT CYLINDER & HAND PUMP SETS**

FREE G2535L GAUGE AND GA-3 ADAPTOR
WITH ANY SET PURCHASED FOR SAFE OPERATIONS

- Ideal where space is restricted
- Single-acting, spring return cylinder
- 25-50 ton capacity, 26-362 mm stroke
- With two speed lightweight or steel hand pump and 1,8 metres safety hose

SET PRICE STARTS AT :

\$791,-

**HOLLOW PLUNGER CYLINDER & HAND PUMP SETS**

FREE G2535L GAUGE AND GA-3 ADAPTOR
WITH ANY SET PURCHASED FOR SAFE OPERATIONS

- For pushing and pulling applications
- Single-acting, spring return cylinder
- 25-50 ton capacity, 26-362 mm stroke
- Center hole 26,9-33,3 mm
- With two speed lightweight or steel hand pump and 1,8 metres safety hose

SET PRICE STARTS AT :

\$1051,-

20-50 ton, Hydraulic Pump-Cylinder Sets

The Quickest and Easiest Way to Start!

RC-Series, General Purpose Cylinder:

- Collar threads, plunger threads and base mounting holes.
- Designed for use in all positions.
- Cylinders are equipped with hardened removable grooved saddles.

RSM-Series, Low Height Cylinder:

- Extremely low height for use in confined areas.
- Mounting holes permit easy fixturing.
- Grooved plunger ends require no saddle.

RCH-Series, Hollow Plunger Cylinder:

- Hollow plunger design allows for both pull and push forces.
- Collar threads for easy fixturing.

P-392 Lightweight Hand Pump:

- With durable glass-filled nylon reservoir and nylon encapsulated aluminium pump base.
- Internal pressure relief valve for overload protection.
- Usable oil capacity 901 cm³.



P-80 Steel Hand Pump

- Internal pressure relief valve for overload protection.
- Usable oil capacity 2200 cm³.

HC-7206 High Pressure Safety Hoses

- 1,8 m length
- Maximum operating 700 bar pressure
- Polyurethane outside jacket.

**FREE G2535L GAUGE + GA-3 ADAPTOR
WITH ANY SET PURCHASED FOR SAFE OPERATIONS.**

Capacity ton (kN)	Cylinder Stroke (mm)	Col- lapsed Height (mm)	Center Hole Ø (mm)	Set Model Number	Set-Components					Special price* (US \$)
					Cylinder	 (kg)	Hand Pump	 (kg)	Safety Hose	



RC-Serie, Single-acting general purpose cylinder with light weight hand pump and hose

25 (232)	26	139	-	SRC-251	RC-251	5,9	P-392	4,1	HC-7206	860,-
	50	165	-	SRC-252	RC-252	6,4	P-392	4,1	HC-7206	892,-
	102	215	-	SRC-254	RC-254	8,2	P-392	4,1	HC-7206	943,-
	158	273	-	SRC-256	RC-256	10,0	P-392	4,1	HC-7206	995,-
	210	323	-	SRC-258	RC-258	12,2	P-392	4,1	HC-7206	1081,-
	261	374	-	SRC-2510	RC-2510	14,1	P-392	4,1	HC-7206	1191,-
	311	425	-	SRC-2512	RC-2512	16,3	P-392	4,1	HC-7206	1283,-
	362	476	-	SRC-2514	RC-2514	17,7	P-392	4,1	HC-7206	1322,-



RC-Serie, Single-acting general purpose cylinder with steel hand pump and hose

50 (498)	51	176	-	SRC-502	RC-502	15,0	P-80	10,9	HC-7206	1423,-
	101	227	-	SRC-504	RC-504	19,1	P-80	10,9	HC-7206	1490,-
	159	282	-	SRC-506	RC-506	23,1	P-80	10,9	HC-7206	1577,-



RSM-Serie, Single-acting low height cylinder with lightweight hand pump and hose

20 (201)	11	51	-	SSM-200	RSM-200	3,1	P-392	4,1	HC-7206	791,-
30 (295)	13	58	-	SSM-300	RSM-300	4,5	P-392	4,1	HC-7206	905,-
45 (435)	16	66	-	SSM-500	RSM-500	6,8	P-392	4,1	HC-7206	1018,-



RCH-Serie, Single-acting hollow plunger cylinder with lightweight hand pump and hose

20 (215)	49	162	26,9	SCH-202	RCH-202	7,7	P-392	4,1	HC-7206	1051,-
	155	306	26,9	SCH-206	RCH-206	14,1	P-392	4,1	HC-7206	1504,-
30 (326)	64	178	33,3	SCH-302	RCH-302	10,9	P-392	4,1	HC-7206	1130,-
	155	330	33,3	SCH-306	RCH-306	21,8	P-392	4,1	HC-7206	1530,-



Your Enerpac Distributor:

www.enerpac.com
info@enerpac.com

Enerpac Middle East FZE
P.O. Box 18004
Jebel Ali Free Zone
Dubai, UAE

Tel: 00 971 4 887 2686
Fax: 00 971 4 887 2687